



iiD 2 Secure

IID-TS700

Three Roller Gates

FEATURES

- 304/316 stainless steel
- Arm lowering when power down (semi- and full-automatic versions)
- Arm raising after power down (full automatic version)
- Compatible with any access control system
- IN/OUT reader option (reader purchased separately)
- Various operation modes (access controlled in/out, free egress/entry, one-way access)
- Indicator lights
- Indoor/outdoor operation
- Size and shapes can be customized



BASIC PARAMETERS

Finish	304/316 stainless steel
Safety	fail safe (free exit/entry)
Capacity	20 to 30 persons per minute
Mechanical operating mode	manual, semi-automatic, full automatic
Direction	single or bid-directional
Controlled operating mode	free entry/exit, controlled entry/exit, no entry/exit, or any combination.
Opening/closing time	0.2 seconds
Operating time after power on	3s semi-automatic (-SA)
8s full automatic (-FA)	adjustable
MCBF (mean cycles between failure)	more than 3 million
Indicator lights	LED directional arrow, green
LED "X" no pass, red	yes
Controls	dry contact/+12Vdc level or pulse input signal for entry and exit

ELECTRICAL

Operating voltage	110Vac/220Vac (±10%) (specify at time of order)
Power consumption	24W

ENVIRONMENTAL

Operating environment	indoor, outdoor with rain shield/canopy
Operating temperature	14°F to 122°F [-10°C to 50°C]
Storage temperature	-4°F to 140°F [-20°C to 60°C]
Operating humidity	20% to 95% (non-condensing)
Storage humidity	20% to 95% (non-condensing)
Ingress protection	IP54

PHYSICAL CHARACTERISTICS

Unit size	47.25"(D) × 11"(W) × 38.5"(H) 120cm(D) × 28cm(W) × 98cm(H)
Arm length	19.5" to 21.5" [50cm to 55cm]
Weight	132 lbs [60kg] for "-M" type 132 lbs [60kg] for "-SA" type 142 lbs [64.4kg] for "-FA" type

PART NUMBERS

IID-TS700-M	manual tripod turnstile, style 03
IID-TS700-SA	semi-automatic tripod turnstile, style 03
IID-TS700-FA	full automatic tripod turnstile, style 03

Address: Heemdtedestraat 16 Amsterdam, Netherlands

Phone Number: +31614762425 | E-mail: Info@iid2secure.nl | Website: www.iid2secure.nl